




APPLICATIONS

HL Linear diffused light series media tube is high brightness and easy installation for architectural outdoor solution. Used milky cover and milky endcap, build in DMX512 Module and auto-programming. The modular system Available in 300mm, 500mm or 1000mm lengths and can be customized as per project's requirement. Two installation way can be selected, fixed clip or U Channel. And all cables can be hidden into channel IP67-rated, UV resistant and designed to withstand outdoor element, applicable for various architectural environment.


SPECIFICATIONS

MOUNTING	:	Surface mounted
LAMP DESCRIPTION	:	12W/m SMD LED chip
COLOR TEMPERATURE	:	RGB/2700/3000/4000/5000K
OPERATING VOLTAGE	:	24V DC
OPERATING TEMP.	:	-35°C + 55°C
ENVIRONMENTAL RATINGS	:	IP67



OPTICAL

DIFFUSER	:	Opal PC cover
AIMING	:	Fixed
LIGHT DISTRIBUTION	:	Symmetric
BEAM ANGLE	:	120°



ELECTRICAL

TRANSFORMER	:	Integral
TRANSFORMER MOUNTING	:	Integral
TRANSFORMER TYPE	:	Electronic AC100-240V 50/60Hz
EMERGENCY	:	NA
DIMMING	:	Non Dimmable, DMX512
LUMEN	:	68-98 lm/W @4000K, 30-40lm/W @ RGB
CRI	:	80+

PHYSICAL

DIMENSION	:	1000 x 33.8 x 64.4 mm
BODY MATERIAL	:	6063-T5 Aluminum
BODY COLOR	:	Black, White, Grey, Light Blue, Gold

PRODUCT SELECTION GUIDE

PRODUCT	COLOR TEMP	POWER	DRIVER	BODY COLOR	ACCESSORIES
HL LD 12	RGB - RGB	12 - 12W/m	ND - Non-Dimmable DX - DMX512	BK - Black	XX - XXX
	27 - 2700 K			WH - White	
	30 - 3000 K			GR - Grey	
	40 - 4000 K			LB - Light Blue	
	50 - 5000 K			GL - Gold	

RoHS



IP67

Ordering Code

HL LD 12 - RGB - 12 - ND - BK - XX

Consult factory / Representative for Custom Details