



APPLICATIONS

Fashion store, chain store, shopping mall;
Showrooms, art galleries, villas.

LED Surface mounded Down light luminaire with die-cast Aluminum alloy in white powder coating finish.

SPECIFICATIONS

NO OF HEAD	:	1
MOUNTING	:	Surfacemounted
LAMP DESCRIPTION	:	30 SMD chip
COLOR TEMPERATURE	:	2700/3000/4000/5000K
OPERATING VOLTAGE	:	100-240V 50/60Hz
OPERATING TEMP.	:	-30°C + 40°C
ENVIRONMENTAL RATINGS	:	IP40

OPTICAL

OPTICS	:	Lens
AIMING	:	Adjustable
LIGHT DISTRIBUTION	:	Symmetric
BEAM ANGLE	:	13°/30°/46°

ELECTRICAL

TRANSFORMER	:	To be ordered seperately
TRANSFORMER MOUNTING	:	Remote
TRANSFORMER TYPE	:	Electronic AC100-240V 50/60Hz - DC1500mA
EMERGENCY	:	NA
DIMMING	:	Non Dimmable, Dali, 1-10v, Triac

PHYSICAL

DIMENSION	:	126 mm x 86 mm x 134 mm (Ø50 mm)
BODY MATERIAL	:	Aluminum Alloy
BODY COLOR	:	Black, Silver, White



PRODUCT SELECTION GUIDE

PRODUCT	COLOR TEMP	POWER	OPTICS	DRIVER	BODY COLOR	REFLECTOR	ACCESSORIES
HL 4028A 30	2700 K	30 W	13- 13°	ND - Non-Dimmable	BL - Black	BL - Black	XXX
	3000 K		30- 30°	DA - DALI	SL - Silver	WH - White	
	4000 K		46- 46°	AN - Analogue (0-10v)	WH - White	XX - Custom	
	5000 K			TR - Triac	XX - Custom		

Ordering Code

HL 4028A 30 - 2700 K - 30W - 13 - ND - BL - BL - XX

Consult factory / Representative for Custom Details



LUMINAIRE LUMEN

2700 K /1800lm	Ra90
3000 K /1950lm	Ra90
4000 K /2242lm	Ra80
5000 K /2550lm	Ra70

RoHS



IP40