




APPLICATIONS

Fashion store, chain store, shopping mall;
Showrooms, art galleries, villas.

LED Down light luminaire with die-cast
Aluminum alloy in white powder coating finish.

SPECIFICATIONS

NO OF HEAD	:	1
MOUNTING	:	Ceiling recessed
LAMP DESCRIPTION	:	2W SMD chip
COLOR TEMPERATURE	:	2700/3000/4000/5000K
OPERATING VOLTAGE	:	100-240V 50/60Hz
OPERATING TEMP.	:	-30°C + 40°C
ENVIRONMENTAL RATINGS	:	IP40



OPTICAL

OPTICS	:	Lens
AIMING	:	Fixed
LIGHT DISTRIBUTION	:	Symmetric
BEAM ANGLE	:	17°/26°/40°

ELECTRICAL

TRANSFORMER	:	To be ordered seperately
TRANSFORMER MOUNTING	:	Remote
TRANSFORMER TYPE	:	Electronic AC100-240V 50/60Hz - DC500mA
EMERGENCY	:	NA
DIMMING	:	Non Dimmable, Dali, 1-10v, Triac

PHYSICAL

DIMENSION	:	42 mm x 75 mm (Ø35 mm)
BODY MATERIAL	:	Aluminum Alloy
BODY COLOR	:	Black, Silver, White

LUMINAIRE LUMEN

■ 2700 K /145lm	Ra90
■ 3000 K /156lm	Ra90
■ 4000 K /177lm	Ra80
■ 5000 K /198lm	Ra70

PRODUCT SELECTION GUIDE

PRODUCT	COLOR TEMP	POWER	OPTICS	DRIVER	BODY COLOR	REFLECTOR	ACCESSORIES
HL 5040 02	2700 K	2W	17- 17°	ND - Non-Dimmable	BL - Black	BL - Black	XXX
	3000 K		26 - 26°	DA - DALI	SL - Silver	WH - White	
	4000 K		40 - 40°	AN - Analogue (0-10v)	WH - White	XX - Custom	
	5000 K			TR - Triac	XX - Custom		

Ordering Code

HL 5040 02 - 2700 K - 2W - 17 - ND - BL - BL - XX

Consult factory / Representative for Custom Details

RoHS



IP40