



APPLICATIONS

Fashion store, chain store, shopping mall;
Showrooms, art galleries, villas.

LED Down light luminaire with die-cast
Aluminum alloy in white powder coating finish.

SPECIFICATIONS

NO OF HEAD	:	1
MOUNTING	:	Ceiling recessed
LAMP DESCRIPTION	:	42W COB chip
COLOR TEMPERATURE	:	2700/3000/4000/5000K
OPERATING VOLTAGE	:	100-240V 50/60Hz
OPERATING TEMP.	:	-30°C + 40°C
ENVIRONMENTAL RATINGS	:	IP40

OPTICAL

OPTICS	:	Lens
AIMING	:	Fixed
LIGHT DISTRIBUTION	:	Symmetric
BEAM ANGLE	:	15°/24°/38°/60°

ELECTRICAL

TRANSFORMER	:	To be ordered separately
TRANSFORMER MOUNTING	:	Remote
TRANSFORMER TYPE	:	Electronic AC100-240V 50/60Hz - DC1000mA
EMERGENCY	:	NA
DIMMING	:	Non Dimmable, Dali, 1-10v, Triac

PHYSICAL

DIMENSION	:	142 mm x 64 mm (Ø130mm)
BODY MATERIAL	:	Aluminum Alloy
BODY COLOR	:	Black, Silver, White



PRODUCT SELECTION GUIDE

PRODUCT	COLOR TEMP	POWER	OPTICS	DRIVER	BODY COLOR	REFLECTOR	ACCESSORIES
HL 5080 42	2700 K	42W	15- 15°	ND - Non-Dimmable	BL - Black	BL - Black	FG - Frosted Glass
	3000 K		24 - 24°	DA - Dali	SL - Silver	WH - White	CG - Clear Glass
	4000 K		38 - 38°	AN - Analogue (0-10v)	WH - White	XX - Custom	
	5000 K		60 - 60°	TR - Triac	XX - Custom		

Ordering Code

HL 5080 42 - 2700 K - 42W - 15 - ND - BL - BL - FG

Consult factory / Representative for Custom Details



Ø130mm

LUMINAIRE LUMEN

■ 2700 K /3150lm	Ra90
■ 3000 K /3360lm	Ra90
■ 4000 K /3570lm	Ra80
■ 5000 K /3780lm	Ra70

RoHS



IP40