



APPLICATIONS

Fashion store, chain store, shopping mall;
Showrooms, art galleries, villas.

LED Down light luminaire with die-cast
Aluminum alloy in white powder coating finish.

SPECIFICATIONS

| | | |
|-----------------------|---|----------------------|
| NO OF HEAD | : | 1 |
| MOUNTING | : | Ceiling recessed |
| LAMP DESCRIPTION | : | 15W COB chip |
| COLOR TEMPERATURE | : | 2700/3000/4000/5000K |
| OPERATING VOLTAGE | : | 100-240V 50/60Hz |
| OPERATING TEMP. | : | -30°C + 40°C |
| ENVIRONMENTAL RATINGS | : | IP40 |

OPTICAL

| | | |
|--------------------|---|-----------|
| OPTICS | : | Lens |
| AIMING | : | Fixed |
| LIGHT DISTRIBUTION | : | Symmetric |
| BEAM ANGLE | : | 15°/25° |

ELECTRICAL

| | | |
|----------------------|---|---|
| TRANSFORMER | : | To be ordered separately |
| TRANSFORMER MOUNTING | : | Remote |
| TRANSFORMER TYPE | : | Electronic AC100-240V 50/60Hz - DC350mA |
| EMERGENCY | : | NA |
| DIMMING | : | Non Dimmable, Dali, 1-10v, Triac |

PHYSICAL

| | | |
|---------------|---|---------------------------|
| DIMENSION | : | 90 mm x 116 mm (Ø80 mm) |
| BODY MATERIAL | : | Aluminum Alloy |
| BODY COLOR | : | Black, Silver, White |


PRODUCT SELECTION GUIDE

| PRODUCT | COLOR TEMP | POWER | OPTICS | DRIVER | BODY COLOR | REFLECTOR | ACCESSORIES |
|------------|------------|-------|-----------------------|-------------------|-------------|------------|--------------------|
| HL 6003 15 | 2700 K | 15 W | 15- 15° | ND - Non-Dimmable | BL - Black | BL - Black | FG - Frosted Glass |
| | 3000 K | | 25 - 25° | DA - Dali | SL - Silver | WH - White | CG - Clear Glass |
| | 4000 K | | AN - Analogue (0-10v) | WH - White | XX - Custom | | |
| | 5000 K | | TR - Triac | XX - Custom | | | |

Ordering Code

HL 6003 15 - 2700 K - 15W - 15 - ND - BL - BL - FG

Consult factory / Representative for Custom Details



LUMINAIRE LUMEN

| | |
|------------------|------|
| ■ 2700 K /1065lm | Ra90 |
| ■ 3000 K /1170lm | Ra90 |
| ■ 4000 K /1320lm | Ra80 |
| ■ 5000 K /1425lm | Ra70 |

RoHS



IP40