




APPLICATIONS

Fashion store, chain store, shopping mall;
Showrooms, art galleries.

LED Linear downlight with High pressure extruded aluminum construction. High transmittance PMMA diffuser specially designed for LED light sources creating smooth and uniform lighting distributions.

SPECIFICATIONS

NO OF HEAD	:	1
MOUNTING	:	Recessed
LAMP DESCRIPTION	:	15W SMD chip
COLOR TEMPERATURE	:	3000/4000K
OPERATING VOLTAGE	:	100-240V 50/60Hz
OPERATING TEMP.	:	-30°C + 40°C
ENVIRONMENTAL RATINGS	:	IP40



OPTICAL

OPTICS	:	Glass
AIMING	:	Fixed
LIGHT DISTRIBUTION	:	Symmetric
BEAM ANGLE	:	Medium

ELECTRICAL

TRANSFORMER	:	To be ordered separately
TRANSFORMER MOUNTING	:	Remote
TRANSFORMER TYPE	:	Electronic AC100-240V 50/60Hz - DC350mA
EMERGENCY	:	NA
DIMMING	:	Non Dimmable, Dali, 1-10v, Triac

PHYSICAL

DIMENSION	:	624 mm x 56 mm x 48 mm
BODY MATERIAL	:	Aluminum body
BODY COLOR	:	Black, Silver, White

LUMINAIRE LUMEN

3000 K /1200lm	Ra90
4000 K /1275lm	Ra80

PRODUCT SELECTION GUIDE

PRODUCT	COLOR TEMP	POWER	OPTICS	DRIVER	BODY COLOR	REFLECTOR	ACCESSORIES
HL 8016 15	3000 K	15W	M - Medium	ND - Non-Dimmable	BL - Black	BL - Black	XXX
	4000 K			DA - Dali	SL - Silver	WH - White	
				AN - Analogue (0-10v)	WH - White	XX - Custom	
				TR - Triac	XX - Custom		

Ordering Code

HL 8016 15 - 3000 K - 15W - M - ND - BL - BL - XX

Consult factory / Representative for Custom Details

RoHS



IP40