



APPLICATIONS

Fashion store, chain store, shopping mall;
Showrooms, art galleries.

LED Linear downlight with High pressure extruded aluminum construction. High transmittance PMMA diffuser specially designed for LED light sources creating smooth and uniform lighting distributions.

SPECIFICATIONS

NO OF HEAD	:	1
MOUNTING	:	Suspended
LAMP DESCRIPTION	:	19W SMD chip
COLOR TEMPERATURE	:	3000/4000K
OPERATING VOLTAGE	:	100-240V 50/60Hz
OPERATING TEMP.	:	-30°C + 40°C
ENVIRONMENTAL RATINGS	:	IP40

OPTICAL


OPTICS	:	Glass
AIMING	:	Fixed
LIGHT DISTRIBUTION	:	Symmetric
BEAM ANGLE	:	Medium

ELECTRICAL

TRANSFORMER	:	To be ordered separately
TRANSFORMER MOUNTING	:	Remote
TRANSFORMER TYPE	:	Electronic AC100-240V 50/60Hz - DC450mA
EMERGENCY	:	NA
DIMMING	:	Non Dimmable, Dali, 1-10v, Triac

PHYSICAL

DIMENSION	:	1199 mm x 148 mm x 29 mm
BODY MATERIAL	:	Aluminum body
BODY COLOR	:	Black, Silver, White



LUMINAIRE LUMEN

3000 K / 1500lm	Ra90
4000 K / 1600lm	Ra80

PRODUCT SELECTION GUIDE

PRODUCT	COLOR TEMP	POWER	OPTICS	DRIVER	BODY COLOR	REFLECTOR	ACCESSORIES
HL 8018B 19	3000 K	19W	M - Medium	ND - Non-Dimmable	BL - Black	BL - Black	XXX
	4000 K			DA - Dali	SL - Silver	WH - White	
				AN - Analogue (0-10v)	WH - White	XX - Custom	
				TR - Triac	XX - Custom		

Ordering Code

HL 8018B 19 - 3000 K - 19W - M - ND - BL - BL - XX

Consult factory / Representative for Custom Details

RoHS

CE

IP40