



APPLICATIONS

Fashion store, chain store, shopping mall;
Showrooms, art galleries.

LED Linear downlight with finland
Ledil top quality, High thermal conductive
aluminum body metal black surface coating.

SPECIFICATIONS

NO OF HEAD	:	1
MOUNTING	:	Ceiling recessed
LAMP DESCRIPTION	:	15W SMD chip
COLOR TEMPERATURE	:	2700/3000/4000/5000K
OPERATING VOLTAGE	:	100-240V 50/60Hz
OPERATING TEMP.	:	-30°C + 40°C
ENVIRONMENTAL RATINGS	:	IP40

OPTICAL

OPTICS	:	Glass
AIMING	:	Fixed
LIGHT DISTRIBUTION	:	Asymmetric
BEAM ANGLE	:	30°

ELECTRICAL

TRANSFORMER	:	To be ordered seperately
TRANSFORMER MOUNTING	:	Remote
TRANSFORMER TYPE	:	Electronic AC100-240V 50/60Hz - DC700mA
EMERGENCY	:	NA
DIMMING	:	Non Dimmable, Dali, 1-10v, Triac

PHYSICAL

DIMENSION	:	500 mm x 35 mm
BODY MATERIAL	:	Aluminum body
BODY COLOR	:	Black, Silver, White


PRODUCT SELECTION GUIDE

PRODUCT	COLOR TEMP	POWER	OPTICS	DRIVER	BODY COLOR	REFLECTOR	ACCESSORIES
HL 8027 15	2700 K	15W	30- 30°	ND - Non-Dimmable	BL - Black	BL - Black	XXX
	3000 K			DA - Dali	SL - Silver	WH - White	
	4000 K			AN - Analogue (0-10v)	WH - White	XX - Custom	
	5000 K			TR - Triac	XX - Custom		

Ordering Code

HL 8027 15 - 2700 K - 15W - 30 - ND - BL - BL - XX

Consult factory / Representative for Custom Details



LUMINAIRE LUMEN

2700 K /1050lm	Ra90
3000 K /1170lm	Ra90
4000 K /1320lm	Ra80
5000 K /1470lm	Ra70

RoHS



IP40